

# UIN-D9932BSSH2-E2

32CH/2HDD/H.265 1080p real-time DVR



## 1. Features

- TVI / AHD / DVR / NVR / CVI five-in-one function, multi-mode input, support HD analog video encoding, support HD analog + HD network video input, support pure HD network video input.
- Easily implement network penetration through cloud services and remote monitoring in one step.
- Supports various mobile phone monitoring (iPhone Android).
- Support multiple web browsers (IE / Chrome / Firefox / Safari).
- Support VGA,TV,HDMI output at the same time.
- Powerful network services (supporting DHCP, PPPOE, FTP, DNS, DDNS, NTP, UPNP, Email, etc.), complete supporting facilities (WEB, client, SDK), easily achieve interconnection and interoperability.
- Supports more than 20 languages and breaks the limits of national borders.
- Freely change the startup interface and choose the interface style.
- Support Dana Cloud Taoshi Cloud cloud platform customization.

## 2. Technical parameters

	<b>Model</b>	<b>UIN-D9932BSSH2-E2</b>
<b>system</b>	<b>Master chip</b>	<b>HI3531A</b>
	<b>AD chip</b>	<b>NVP6134C</b>
	<b>RAM</b>	<b>8G</b>
	<b>Compression format</b>	<b>H.265X</b>
	<b>operating system</b>	<b>Embedded Linux operating system</b>
	<b>Input</b>	<b>32</b>
	<b>Preview</b>	<b>32 * 1080N/25fps</b>

<b>video</b>	<b>Coding</b>	<b>32 * 1080N/15fps</b>
	<b>Decoding</b>	<b>16 * 1080N/15fps</b>
	<b>VGA output</b>	<b>1080P</b>
	<b>BNC output</b>	<b>support</b>
	<b>HDMI output</b>	<b>1080P</b>
<b>Playback</b>	<b>Number of real-time recording channels</b>	<b>32-way non-real-time</b>
	<b>Video mode</b>	<b>Timing, manual, motion detection, external alarm</b>
	<b>The number of simultaneous playback</b>	<b>16</b>
	<b>Search mode</b>	<b>Point-in-time search, calendar search, event search, channel search</b>
<b>Backup</b>	<b>USB mobile hard disk, U disk</b>	<b>support</b>
	<b>USB DVD burner</b>	<b>support</b>
	<b>Format</b>	<b>H.26X、AVI</b>
<b>remote access</b>	<b>Browser</b>	<b>Supports multiple web browsers</b>
	<b>Client</b>	<b>Support VMS</b>
	<b>APP</b>	<b>Support for iPhone, Android</b>
<b>storage</b>	<b>HDD number</b>	<b>2</b>
	<b>E-SATA</b>	<b>not support</b>
<b>Network</b>	<b>Network port</b>	<b>10 / 100/1000 Mbps Ethernet (RJ-45)</b>
	<b>Network protocol</b>	<b>TCP/IP, DHCP, DDNS, NTP, SMTP</b>
<b>other</b>	<b>remote control</b>	<b>support</b>
	<b>power supply</b>	<b>DC12V /4A</b>
	<b>Work Temperature</b>	<b>-10° C ~60° C</b>
	<b>Working humidity</b>	<b>10% ~ 90% Humidity</b>