



# IPY-Z45820LDS2T

8 MP 20X PTZ IR Dual-light PTZ Camera

Built-in Mic & Speaker

Human Tracking and Vehicle Detection



## ■ Features

- 1/2.8" Sony CMOS sensor
- 4K resolution 3840 x 2160P
- Low illumination 0.01Lux
- 20x optical zoom
- Smart Human and Vehicle Detection Alarm
- Smart Human Tracking
- Built-in Mic and speaker, two-way audio
- Day/Night, AWB/MWB, BLC, HLC, 2D/3D-DNR, Shutter, IR-CUT
- D-WDR, Flip, Defogging
- Multiply Style OSD Overlay, Motion Detection, Privacy Mask
- RTSP and Onvif 17.06 compatible with many third-party NVR
- H.264/H.265 dual-stream media server
- Easy-to-use P2P Cloud service
- Support user authentication, video data encryption
- Support Alarm Snapshot to Email and FTP
- Multiply WEB browser IE,Firefox,Chrome,Edge,Safari
- Free PC Client, Mobile APP remote access
- RJ45 100mbps network port, IEEE802.3af 48v PoE
- Lightning protection 4000V
- Strong metal water-proof housing, IP66
- 6 pcs Array IR Led , 4 pcs warm light Led
- IR distance 80-100 meters





## ■ Specification

### Camera

Image Sensor	1/2.8" Sony CMOS
Effective Pixels	8 megapixels
Electronic Shutter	AUTO, 1/10s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON)
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Manual
BLC /HLC	Support
DNR	2D/3D DNR
Other	Image adjust,Flip

### Encode

Video Standard	H.264/H.265/Mjpeg
Video Resolution	MainStream:20fps@8MP(3840x2160),30fps@6MP(3072x2048)/5MP(2592x1944)/4MP/3MP/1080P/720P, etc.Sub stream: 720x480/VGA(640x480)/360P/QVGA@30fps,etc.
Video Bitrates	512Kbps - 12Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a/AAC
Two-way audio	Built-in Mic and speaker
Smart Detection	Smart Human and Vehicle Detection

### IR Led

IR Led	6pcsarrayIR Led
Warmlight	4pcs Led
Distance	IR: 80-100M, Warm light: 40-50M

### Lens

Focal length	4.7-94mm
IRIS	F1.6-3.5
View angle	64 - 2.9 °
Zoom	20x optical zoom

### Optional Function

High power PoE+

### PTZ

Pan/Tilt Range	Pan: 0° ~ 360°; Tilt: -5° ~ 90°
Preset Point	256
Control Speed	Pan: 0.5° ~25° /s; Tilt: 0.5° ~25° /s
A-B	
Auto Cruising	Support 8 groupspatrol,Max. 16 presets in group
Power on Action	Preset/Scan/Cruise
Power-off Recovery	Support
Smart Tracking	Human Detection Tracking together with patrol

### Network Services

Protocol	HTTP/RTSP/FTP/SMTP/DHCP/NTP/NFS/RTMP, etc.
P2P	Yes
Web	IE, Firefox, Chrome, Edge, Safari
Media	CMS, Android, IOS
ONVIF	17.06 compatible

### General

Network Port	1-RJ45, 100Mbps,PoE 48V in
Power Supply	12 VDC ± 10%2A
Power Consumption	<22W
Operating Temp.	-30°C-(+60)°C, 10%-90%RH
Size	5inch
Weight	






**IPY-Z45820LDS2T**  
8 MP 20X PTZ IR Dual-light PTZ Camera

■ **Available Model**

IPY-Z45620LDS2T (Zoom 20X)

IPY-Z45820LDS2T (Zoom 20X)

■ **Dimension**




■ **Accessory**

■ **Optional**



■ **Celling mount: (optional)**



Uin Technology Co., Ltd.

+86-871 63586112

www.uin-tech.com

4F,Block 7 Lijincheng High Tech Garden,Longhua District,Shenzhen China

